

HAFCO-METALMASTER EB-280DS




Swivel Head Metal Cutting Band Saw




HAFCO-METALMASTER Swivel Head Metal Cutting Band Saw EB-280DS



Control Panel



Variable Feed Control Valve



Blade Tension Gauge



Dual Mitre Swivel Head



Quick Action Clamp Lever




Motor and Gearbox




Roller Support



Coolant Pump



Swivel Head Degree Scale



Lock Lever



Control Panel

Features

- 245 x 180mm rectangular capacity
- Larger cutting capacity than conventional cold saws
- Swivel head double mitre cut to 45° right & left, 60° right
- Quick action lock/release lever for swivel head
- Heavy-duty gear drive system
- Control panel mounted up high for convenient & easy access
- Heavy duty hydraulic down feed cylinder accessible from front of machine for convenient & easy access
- Ball bearing blade guides ensures minimal blade clearance wear and increases blade life due to less friction
- Blade cleaning brush incorporated into blade guide system
- Quick-action lock/release vice
- Unique sliding vice design for dual mitre operation
- Coolant system for cutting efficiency and blade life
- Material support roller for long stock

HAFCO-METALMASTER Swivel Head Metal Cutting Band Saw EB-280DS

- User friendly blade tension system with gauge
- 2-speed motor enabling blade speeds of 45 & 90mpm
- Vibration free, low noise operation ensures clean & high precision cuts
- Machine stand with integrated cooling fitted as standard

Specifications

ORDER CODE	B063
MODEL	EB-280DS
Operation Type	Swivel Head - Dual Mitre
Round @ 90° (mm)	225
Round @ 45° (mm)	160
Round @ 60° (mm)	100
Square @ 90° (mm)	180
Square @ 45° (mm)	160
Square @ 60° (mm)	100
Rectangle (W x H) @ 90° (mm)	245 x 180
Rectangle (W x H) @ 45° (mm)	160 x 160
Rectangle (W x H) @ 60° (mm)	100 x 100
Coolant System	Yes
Table Working Height (mm)	965
Cutting Head Beam Type	Manual
Cutting Head Beam Return	Manual Return
Cutting Head Down Feed Control	Adjustable Hydraulic
Vice Clamping Fixture	Manual - Quick Action
Bundle Cutting Fixture	~
Blade Steps / Speeds (M/Min)	45-90
Blade Size (L x W x T) (mm)	2480 x 27 x 0.9
Motor Power (kW / hp)	1.1 / 1.5
Voltage / Amperage (V / amp)	415
Nett Weight (kg)	280