

HAFCO-METALMASTER GHD-22



Industrial 3MT Geared Head Drilling Machine

Ø31.5mm Drilling Capacity



HAFCO-METALMASTER Industrial 3MT Geared Head Drilling Machine GHD-22



Left View



High Low With Forward and Reverse Switch



Spindle Speeds



Interlocked Spindle Safety Guard



Quill Handle



T Slotted Work Table Rotates 360 Degrees



Rack and Pinion Wind Up Drill Head



Drill Chuck

Description

Have you had enough of drilling machines that can slip via their pulley & drive belt system? Then if this is happening to your drill in the workshop, I urge you to consider this GHD-22 Industrial 3 morse taper geared head drilling machine to eliminate that drive slippage.

This drill has all the common features that is required for e.g., large cast drill table with T-slots and rotates 360°, drilling speeds from 105 to 2900rpm, drill depth stop for accurate repeatability and a 16mm drill chuck with adaptor. Another notable feature to mention is that just like the rack & pinion drill table height adjustment, the drill head can also be adjusted up or down to suit the height for each operator.

Features

- Ideal for industrial or workshop use
- Geared head drilling machine with 3 morse taper spindle
- 8 drilling speeds from 105 - 2900 rpm
- High/low with forward & reverse switch
- Helical cut gears for quiet & smooth operation
- Interlocked spindle safety guard
- Rack and pinion wind-up drill head
- Rack & pinion table height adjustment with locking lever
- Thick walled column ensuring greater rigidity
- Drill ejector lever
- Safety emergency stop/reset switch
- Table rotates 360°
- Drilling depth stop setting with scale
- T slotted work table

HAFCO-METALMASTER Industrial 3MT Geared Head Drilling Machine GHD-22

Includes

- 16mm keyed drill chuck and arbor
- Chuck key to suit
- Drill drift tool to remove drill chuck or taper shank drills
- Interlocked spindle safety guard

Specifications

ORDER CODE	D170
MODEL	GHD-22
Drilling Capacity (mm)	Ø31.5
Thread Tapping Capacity (Metric)	~
Spindle Taper (MT)	3
Spindle Travel (mm)	120
Throat Depth (mm)	255
Quill Diameter (mm)	55
Column Diameter (mm)	100
Spindle To Table (mm)	830
Spindle To Base (mm)	1240
Table (Type)	Rectangle
Table Size (mm)	350 x 500
T-Slot Size (mm)	14
Automatic Quill Feed (mm/rev)	~
Work Light (Includes)	~
Coolant System (Includes)	~
Spindle Speed Steps (No.)	8
Spindle Speed Range (rpm)	105 ~ 2900
Motor Power (kW / hp)	0.9 / 1.2
Voltage / Amperage (V / amp)	415
Full Height (mm)	1800
Nett Weight (kg)	220