

MACNAUGHT P3 powerlube® P3-01C



Air Operated - Grease Gun

Suits 20kg Drum



MACNAUGHT Air Operated - Grease Gun P3 powerlube® P3-01C

Description

The P3 POWERLUBE® P3-01C is the ultimate in high pressure, air-powered greasing. With models available to suit containers from 12.5kg (28 lbs.) to 20 kg (48 lbs.), it is fitted with a 50:1 ratio air motor which can run off most small compressors to provide fast, continuous greasing. The P3 POWERLUBE is also suitable for underground coal mine applications.

For Warranty Terms and Conditions - [click here](#)

Features

- Quiet, non-corroding air motor
- Grease viscosity: up to NLGI No.2
- Wetted components: zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- Output: approx. 460 g/min (16 oz/min)
- Max. air pressure: 1,030 kPa (150 psi, 10.3 bar)
- Min. air pressure: 400 kPa (60 psi, 4 bar)
- Min. compressor size: 0.08 m³/min (3 cfm)
- Air inlet/fluid outlet: 1/4" NPT (F)
- Pump ratio: 50:1 (grease pressure is 50 times air)
- B2 gun pressure: up to 69,000 kPa (10,000 psi, 690 bar) (boost pressure)
- Hose thread: 1/4" NPT (M) TA-7K Filter & Regulator Kit
- Low air consumption
- No air line lubricator required
- Rubber edged follower plate
- 4m (13 ft.) x 6 mm (1/4") ID delivery hose
- B2 booster gun with 360° ZSB swivel
- Fully serviceable
- 10 Year Macnaught Warranty

Specifications

ORDER CODE	G062
MODEL	P3 powerlube® P3-01C
Type	Air Operated Grease Gun
Size	20kg Drum