

## HAFCO-METALMASTER EB-320DS



### Swivel Head Metal Cutting Band Saw & Conveyor System Package Deal



## HAFCO-METALMASTER Swivel Head Metal Cutting Band Saw & Conveyor System Package Deal EB-320DS




Adjustable Automatic Feed



Blade Tension Gauge



Control Panel



Dual Mitre Swivel Head



Motor and Gearbox Drive



Quick Action Clamp Lever



Wire Wheel and Roller  
Bearing Blade Guides



Coolant System

### Features

- 310 x 205mm rectangular capacity
- Larger capacity than conventional cold saws
- Heavy-duty gear drive system
- Ball bearing blade guides ensures minimal blade clearance wear and increases blade life due to less friction
- Blade cleaning brush incorporated into blade guide system
- Swivel head double mitre cut to 45° right & left, 60° right
- Quick action lock/release lever for swivel head
- Coolant system for cutting efficiency and blade life
- Input support roller for long stock
- User friendly blade tension system with gauge
- Adjustable hydraulic cylinder for auto feed
- 2-speed motor enabling blade speeds of 35 & 70mpm
- Vibration free, low noise operation ensures clean & high precision cuts
- Machine stand with integrated cooling fitted as standard
- Quick-action lock/release vice
- Unique sliding vice design for dual mitre operation

## HAFCO-METALMASTER Swivel Head Metal Cutting Band Saw & Conveyor System Package Deal EB-320DS

### Includes

- 1 x EB320DS band saw
- 2 x 290mm wide x 3000mm long roller conveyors
- 4 x Conveyor stands
- 1 x 3000mm length stop

### Specifications

<b>ORDER CODE</b>	K002
<b>MODEL</b>	EB-320DS Package Deal
<b>Operation Type</b>	Swivel Head - Dual Mitre
<b>Round @ 90° (mm)</b>	255
<b>Round @ 45° (mm)</b>	220
<b>Round @ 60° (mm)</b>	125
<b>Square @ 90° (mm)</b>	205
<b>Square @ 45° (mm)</b>	200
<b>Square @ 60° (mm)</b>	125
<b>Rectangle (W x H) @ 90° (mm)</b>	310 x 205
<b>Rectangle (W x H) @ 45° (mm)</b>	205 x 200
<b>Rectangle (W x H) @ 60° (mm)</b>	125 x 125
<b>Coolant System</b>	Yes
<b>Table Working Height (mm)</b>	950
<b>Cutting Head Beam Type</b>	Manual
<b>Cutting Head Beam Return</b>	Manual Return
<b>Cutting Head Down Feed Control</b>	Adjustable Hydraulic
<b>Vice Clamping Fixture</b>	Manual - Quick Action
<b>Bundle Cutting Fixture</b>	~
<b>Blade Steps / Speeds (M/Min)</b>	35-70
<b>Blade Size (L x W x T) (mm)</b>	2750 x 27 x 0.9
<b>Motor Power (kW / hp)</b>	1.5 / 2
<b>Voltage / Amperage (V / amp)</b>	415
<b>Nett Weight (kg)</b>	360