

METALMASTER QLD Schools / TAFE



HPM-30 Trade Hydraulic & Pneumatic Press - 30 Tonne

QLD Contract




METALMASTER HPM-30 Trade Hydraulic & Pneumatic Press - 30 Tonne QLD Schools / TAFE



Robotic Welded Frame



Hydraulic Pneumatic Hand Pump



Metric / Imperial Pressure Gauge



Table Pins With Safety Clips



Dual Purpose Pressing Blocks



Pneumatic Valve Control



Horizontal Sliding Ram



Ram Top View With Bearing Slide



Sliding Ram With Handle



Includes Removable Ram Top Cap



Front View



Left View




Rear View



Right Side View



left Side View



Dimensions

METALMASTER HPM-30 Trade Hydraulic & Pneumatic Press - 30 Tonne QLD Schools / TAFE




P030 PDS 2B Bush Driver Set



P031 PDS 3BS Bearing Race Seal Driver Set



P455 PBA 60 Pressbrake Attachment Suits Hydraulic Presses



P1401 PPK 20 Steel Press Pin Driver Set 11 piece



P1404 PGM 30 Hydraulic Press Guard

Description

The Metalmaster HPM-30 30 tonne trade press has a variety of uses, ideal for removing and installing bushes, ball joints, bearings, gears, pulleys etc. The HPM-30 is pneumatically or hand operated for easy use and also has the added feature of a sliding head which can be moved to the side allowing for those offset pressing jobs.

This 30 tonne press has a fully robotic welded frame for the highest quality, accuracy and extra rigidity. The press is supplied with a pressure gauge, two heavy duty pressing plates, and can be fitted with an optional pneumatic foot pedal, making it ideal for mechanics, farmers or the serious home workshop.

Features

- Ideal for removing and installing - Bushing, Ball-joints, Bearings, Gears, Pulleys, etc
- Pneumatic or hand operation
- Heavy duty steel construction with robotic fully welded frame
- Hydraulics assembled in a temperature controlled clean room for maximum quality
- Hydraulics individually factory tested prior to shipping.
- Adjustable sliding head up to 200mm travel between the vertical post
- Metric / imperial pressure gauge included
- NOTE: Minimum Air Flow Rate required is 200 liters/minute
- OPTIONAL SAFETY FEATURES
- PGM-30 - Hydraulic Press Guard (P1404)

METALMASTER HPM-30 Trade Hydraulic & Pneumatic Press - 30 Tonne QLD Schools / TAFE**Includes**

- Complete with vee blocks

Specifications

ORDER CODE	K8759
NSW DOE Item No.	~
QLD DOE Item No.	~
MODEL	HPM-30
Capacity (Tonne)	30
Sliding Ram (Yes / No)	Yes
Width Between Front Posts (mm)	535
Width Between Side Posts (mm)	138
Ram To Table (Max.) (mm)	1035
Cylinder Stroke (mm)	155
Ram Diameter (mm)	Ø70
Piston Diameter (mm)	Ø80
Floor Space (W x D x H) (mm)	950 x 700 x 1800
Nett Weight (kg)	200