

HAFCO-WOODMASTER DS-25



Twin Drum Sander

Variable Conveyor Feed Speeds




HAFCO-WOODMASTER Twin Drum Sander DS-25



Conveyor Feed Motor



Twin Drum Sanding System



Variable Table Feed Speed



Magnetic Safety Switch



Thickness Height Gauge



Top Guard Open



Rear View



Switch

Description

Manufactured in Taiwan

Features

- 635mm (25") sanding width capacity
- Twin, dynamically balanced 127mm drums ensure smooth sanding (1 coarse & 1 fine)
- High quality conveyor belt, easy to track for smooth feeding
- Variable speed conveyor drive giving 1.1 m/min to 5.7 m/min
- Sanding workpiece thickness, Min/Max (6 - 127mm)
- 2.2kW / 3hp Induction 240V motor
- Twin Ø100mm (4") dust ports for efficient dust extraction
- DOL starter switch with overload protection and raised red stop

Includes

- Two abrasive belts (80 grit and 120 grit)

HAFCO-WOODMASTER Twin Drum Sander DS-25**Specifications**

ORDER CODE	L129
MODEL	DS-25
Variable Table Feed Speed (m/min)	0.9 - 6
Sanding Drum Speed (rpm)	1600
Belt Size (mm)	2790 x 100
Drum Diameter (mm)	127
Maximum Material Width (mm)	635
Maximum Material Thickness (mm)	127
Minimum Material Thickness (mm)	6
Dust Collector Port Diameter (Qty x mm)	2 x Ø100
Feed Motor Power (hp)	1/8
Motor Power (kW / hp)	2.2 / 3
Voltage / Amperage (V / amp)	240 / 15
Floor Space (W x D x H) (mm)	1130 x 780 x 1360
Nett Weight (kg)	225