

HAFCO-METALMASTER PN-76E



Pipe & Tube Notcher - Linisher


Single Direction C/W 2 Working Stations



HAFCO-METALMASTER Pipe & Tube Notcher - Linisher PN-76E



Swivel Vice From 30 90




Knotching



Quick Action Compound Vice



Top Station For Flat Linishing Deburring



Vice Angle Adjustment



Quick Change Belt System



Removable Front Dust Tray



Left Side View



Right Side View



Rack For Roller Storage

Description

The PN-76E Pipe & Tube Notcher / Linisher is our economy version for notching of tube & pipe with the added versatility of deburring & linishing all types of steels. This notcher comes standard with a single direction motor for maximising the use of the notching & top linishing stations & with a powerful 3Kw 415v motor it will remove material quickly & easily. The machine features a notching vice that allows you to adjust your notch to any angle between 90 to 30 degrees & a spring tension device to maintain continuous belt tension. With the Fast-Change tension system you can quickly change the diameter of the front roller to suit the diameter of the notch you require. The base includes a storage rack for up to 7 sets of notching rollers to keep them within easy reach saving you time when changing between sizes.

HAFCO-METALMASTER Pipe & Tube Notcher - Linisher PN-76E

Features

- Ø20-76mm OD tube notching capacity
- 1/2" - 2-1/2" NB pipe notching capacity
- Powerful 3kW / 4hp, 415V motor with overload protection
- 2 x speed motor 1400rpm for stainless steel, 2800rpm for steel
- Double working stations for Notching & de-burring
- Quick action compound swivel vice from 30-90°
- Heavy duty leadscrew vice for increasing clamp pressure
- Fast change belt system for fast and easy change of grinding rolls – no tools required
- Spring device allows for continuous belt tension
- Solid pedestal stand with built in storage rack for notching rollers

Includes

- 1 notching rollers suitable for the following material sizes
- Ø1-1/4" NB pipe or Ø42mm tube
- 1 x linishing belt

Specifications

ORDER CODE	L850
MODEL	PN-76E
Machine (Type)	Pipe & Tube Notcher - Linisher
Notching Cutter (Type)	Linisher
Tube Capacity (OD) - Mild Steel (mm)	Ø20 - Ø76
Pipe Capacity (NB) - Mild Steel (inch / mm)	1/2" - 2-1/2"
Angle Adjustment (Degree)	30-90°
End Mill Size (inch / mm)	~
Belt Size (mm)	100 x 2000
Belt Speed	1400rpm / 2800rpm
Cutting Speed (rpm)	~
Motor Power (kW / hp)	3 / 4
Voltage (V)	415
Dimensions ((mm))	~
Nett Weight (kg)	160