

HAFCO-METALMASTER HM-54GV



Workshop Turret Milling Machine Inverter Variable Speed, Geared Head - Horizontal & Vertical

Table Travel: (X) - 600mm (Y) - 200mm (Z) - 340mm



HAFCO-METALMASTER Workshop Turret Milling Machine Inverter Variable Speed, Geared Head - Horizontal & Vertical HM-54GV



Left View



Head Controls



3 Axis Digital Readout System




Control Panel With Digital Speed Readout




Vertical Variable Speed Motor



Vertical Spindle With Quill Lock



Safety Cutter Guard




Horizontal Spindle



Horizontal Spindle Support



Horizontal Spindle Control Panel



Horizontal Spindle Speed Chart



Quill Feed-Fine Feed Handles



Fine Feed Quill Dials-Handle



High Low Speed Gear Selector



Concentina Slideway Cover




Tilt Head- 45 Degree

HAFCO-METALMASTER Workshop Turret Milling Machine Inverter Variable Speed, Geared Head - Horizontal & Vertical HM-54GV




Rotating Adjustable Sliding Ram



Work Table Coolant Return



Worklight And Coolant Hose



X Axis Power Feed With Rapid




Table Feed Limit Switch



Adjustable Table Stops



Swivel Table Scale



Hardened Ground Work Table



Z Axis Handle



Z Axis Dial



X Axis Dial



X Axis On Power Feed



Y Axis Dial



Coolant Pump



Included Accessories

HAFCO-METALMASTER Workshop Turret Milling Machine Inverter Variable Speed, Geared Head - Horizontal & Vertical HM-54GV

Description

This HM-54GV geared head vertical and horizontal turret milling machine now includes a inverter variable speed drive on the vertical spindle, with a powerful continuous-load 2.2kW / 3hp vertical motor and a 2hp motor for the horizontal spindle, intended for trade use. The work table is precision made with adjustable dovetail guides and is recognised for its 600mm X axis by 200mm Y axis travel. There is a three armed handle on the side for drilling also incorporating a fine feed control hand wheel on the front for milling. The hi-low geared head selector lever mounted on right side of milling head allows for quick change off speed range.

Other features include 3-Axis digital readout system, taper roller bearing support for the spindle, easy-to-read drilling depth stop, low voltage LED work light, coolant system, X axis power feed unit, drill chuck, 1" & 1-1/4" horizontal arbors, 2 & 3 morse taper adaptors. The combination of generous sized vertical support and rugged cast iron construction throughout reduces vibration and guarantees accurate and chatter-free operation.

Extra Features:

Swivel table

1" & 1-1/4" horizontal arbors

Features

- Electronic inverter variable spindle speeds
 - 3 Axis digital readout system
 - Swivel table left & right with graduated scale
 - Mill head tilts to $\pm 45^\circ$ left to right
 - 450mm horizontally sliding and rotating ram
 - NT30 Horizontal and vertical spindles that are hardened and ground
 - Precision-ground dovetail slide-ways and table
 - Precision milling table incorporating machined T slots
 - Rear concertina slide-way cover
 - Forward and reverse button switch
 - Fine hand wheel operated quill feed
 - Swarf & splash tray
 - Spindle lock for quill
 - Metric dial graduations @ 0.02mm for X , Y & Z-Axis
 - Vertical quill hand-wheel dial graduations @ 0.05mm
 - All slides utilise dovetail construction for maximum rigidity
 - Includes 1" & 1-1/4" arbors for the horizontal spindle
- * Note: X travel maybe reduced due to digital readout scales and safety stops

Includes

- Electronic inverter variable spindle speeds
- 3 Axis digital readout system
- X-Axis power-feed
- Safety cutter guard
- Swarf tray
- Coolant system
- LED work light
- Drill chuck & arbor
- NT30 to 3MT adaptor
- 2MT & 3MT adaptors
- M12 x 1.75mm Drawbar

HAFCO-METALMASTER Workshop Turret Milling Machine Inverter Variable Speed, Geared Head - Horizontal & Vertical HM-54GV

Specifications

ORDER CODE	M579
MODEL	HM-54GV
Digital Readout	3-Axis Digital Readout
Type	Vertical & Horizontal
Table Size (mm)	1000 x 240
Column Type	~
Spindle Taper - Vertical	NT30
Spindle Taper - Horizontal	NT30
Longitudinal Travel (X-Axis) (mm)	600*
Cross Travel (Y-Axis) (mm)	200*
Vertical Travel (Z-Axis) (mm)	340
Type of Slides	Dovetail
Ram Travel (mm)	450
Spindle to Table (mm)	375
Spindle to Base	~
Spindle Travel / Diameter (mm)	120 / 90
Throat Depth (max.) (mm)	640
Tilting Head (Left ~ Right)	±45°
Tilting Head (Forward ~ Back)	Fixed
Drilling Capacity (mm)	40
End Milling Capacity (mm)	25
Face Milling Capacity (mm)	80
Power Feed - Quill (mm/rev)	Manual
Power Feed - Longitudinal (X-Axis) (mm/min)	20 - 2000
Power Feed - Cross (Y-Axis) (mm/min)	~
Power Feed - Vertical (Z-Axis) (mm/min)	~
Table T-Slot Size (inch / mm)	14
Work Table Load Capacity (kg)	160
Spindle Speeds Vertical (No./ rpm)	Variable (100 - 2000)
Spindle Speeds Horizontal (No./ rpm)	9 (60 - 1350)
Spindle Speeds - Universal Head	~
Motor Power - Vertical Spindle (kW / hp)	2.2 / 3
Motor Power - Horizontal Spindle (kW / hp)	1.5 / 2
Motor Power - Universal Head	~
Voltage / Amperage (V / amp)	240 / 10
Nett Weight (kg)	900