

METALMASTER PB-422A

METALMASTER

Manual Panbrake

1250 x 2mm Mild Steel Bending Capacity



METALMASTER Manual Panbrake PB-422A




Digital Angle Readout



Quick Head Adjustment
Handle for Material Thickness



Top Beam Support Stop Lever
and Thickness Adjustment Handle



Removable Extra Long
Fingers



Rear Manual Backgauge



Rear Back Gauge

Features

- 1250mm x 2mm capacity
- Extended fingers allows bending of pans or boxes to a depth of 230mm
- Quick head adjustment mechanism to suit your material thickness
- Ground segmented fingers can be repositioned to suit many applications
- Heavy duty steel fabricated frame provides accurate bends
- Safety top beam support stop lever located on right side of machine
- Grease nipples located on all rotating parts
- Quick action beam adjustment for varying material thickness
- Removable individual bending fingers for pans or boxes
- Mild steel capacity is rated on hot rolled material with 250MPA

Includes

- Includes digital angle readout with CR2032 battery
- Quick Action Beam Head Adjustment for Material Thickness
- Rear manual backgauge

METALMASTER Manual Panbrake PB-422A

Specifications

ORDER CODE	S262
MODEL	PB-422A
Bending Capacity - Mild Steel (mm)	2
Material Length Capacity (mm)	1250
Floor Space (L x W x H) (mm)	1820 x 620 x 1300
Nett Weight (kg)	980