

METALMASTER SRG-90



Manual Sheet Metal Curving Rolls

1270 x 2.5mm Mild Steel Capacity



METALMASTER Manual Sheet Metal Curving Rolls SRG-90



Left View



Rear View



End View



Swivel Top Roll



Rolls with Wiring Grooves



Rear Curving Roll Height Adjustment



Rear Roll Adjustment Scale



Material Thickness Adjustment



Roll Adjustment Handles



Gear Rack

Description

Built for workshops that need reliable rolling performance without the fuss, the SRG-90 delivers the strength, accuracy and durability serious fabricators demand. This heavy-duty manually operated sheet metal curving roll is ideal for rolling cylinders, curved panels, cones and general fabrication work.

The hardened Ø90mm precision-ground SAE 1050 steel rolls produce smooth, accurate curves, while the two driven rolls provide controlled feeding and consistent rolling performance. Its initial pinch design keeps operation simple and efficient for both one-off and repeat fabrication work. The bottom roll height is adjusted via a wedge-type design that moves both sides simultaneously, allowing quick and controlled positioning with a single handle movement.

Integrated wiring grooves add extra versatility, while the quick-action swivel-out top roller allows fast and easy removal of finished cylindrical and conical workpieces.

Need to roll cones and tapered sections? The built-in conical bending device allows trapezoidal or fan-shaped sheet metal to be formed into tapered cone shapes with ease, making the SRG-90 ideal for custom fabrication and specialised rolling applications.

METALMASTER Manual Sheet Metal Curving Rolls SRG-90

With a 1270mm working length and 2.5mm mild steel capacity, rated on 250MPa hot rolled material, the SRG-90 is perfectly suited to fabrication shops, maintenance departments and general sheet metal workshops.

Features

- 1270mm working length with 2.5mm mild steel capacity
- Hardened SAE1050 steel rollers
- Ø90mm precision-ground rolls
- Two driven rolls for smooth rolling performance
- Initial pinch style roll configuration
- Wedge-type bottom roll adjustment
- Integrated wiring grooves (3mm, 6mm & 10mm)
- Quick-action swivel-out top roller
- Built-in conical bending device
- Heavy-duty cast iron end frames
- Capacity rated on 250MPa hot rolled mild steel

Specifications

ORDER CODE	S278
MODEL	SRG-90
Useful Length (mm)	1270
Capacity - Mild Steel (mm)	2.5
Minimum Rolling Diameter (mm)	135
Roll Diameter (mm)	90
Wire Groove Rolls (mm)	3 / 6 / 10
Includes Stand (No / Yes)	Yes
Nett Weight (kg)	465