

## HAFCO-METALMASTER SB-375F



### Industrial Sandblasting Cabinet

Inside Cabinet 910 x 600 x 400-660mm (L x W x H)



**HAFCO-METALMASTER Industrial Sandblasting Cabinet SB-375F**



Lid Open



Side View Lid Open



Side View



Left View



Rear Right View



Rear Left View



Switches for Light and Dust Collector



Gas Strut Door



Gloves



Internal Light with Tear Off Film on Glass



Door Safety Interlock




Inside Work Area



Gun



Hopper with Removable Grates



Abrasive Measuring Valve



Hopper Emptying Hatch

**HAFCO-METALMASTER Industrial Sandblasting Cabinet SB-375F**



Foot Pedal Blasting Switch



Foot Pedal Action Shot



Dust Collector and Filter System



Filter Shaker



Removing Motor Filter Assembly



Dust Collector Emptying Hatch



Motor Filter Assembly Removed



Filter System Connection Lead



Air Intake Breather



Lid Open Latch



Air Pressure Gauge



Air Pressure Gauge Assembly



Solenoid Valve Assembly



Compressed Air Inlet Connection



Included Accessories

## HAFCO-METALMASTER Industrial Sandblasting Cabinet SB-375F

### Description

The SB-375F Heavy-Duty Sandblasting Cabinet is now equipped with an integrated gravity feed metering valve, delivering smooth, controlled abrasive flow to maintain the ideal air-to-media ratio for stronger, more consistent blasting performance with reduced clogging and improved efficiency. Built as a proven workshop performer, it features a front-opening access door for easy loading and handling of workpieces, while a large tempered glass viewing window and internal LED lighting system provide excellent visibility and comfortable operation.

At the rear of the machine, an in-built vacuum extraction system removes fine dust and airborne particles during blasting, ensuring you always have clear vision of your workpiece and a cleaner working environment.

### Features

- Front opening door for easy access
- Integrated gravity feed metering valve ensures smooth, controlled media flow for stronger, more consistent blasting performance
- Powder coated steel construction
- Built in 240V vacuum and filter system at rear of sandblast cabinet
- Internal LED lighting system
- Door safety interlock
- Complete tempered glass screen with replacement shields, gloves, gun & ceramic tips
  
- Requires compressor delivering minimum 24 CFM (680 L/min) @ 100 psi (FAD)
- Recommended to use 3 x 25kg abrasive grit

### Specifications

<b>ORDER CODE</b>	S301
<b>MODEL</b>	SB-375F
<b>Approx. Inside Cabinet Size (L x W x H) (mm)</b>	910 x 600 x 400-660
<b>Internal Light (Type)</b>	LED Light
<b>Recommended Free Air Delivery (FAD) @ 100psi (CFM/L/min)</b>	24 CFM (680 L/min)
<b>Floor Space with Door/Lid Open (L x W x H) (mm)</b>	920 x 1000 x 1920
<b>Nett Weight (kg)</b>	82.50