

SAFEWAY PQV-130V



Safeway Pneumatic Production Vice

130mm Jaw Width



SAFEWAY Safeway Pneumatic Production Vice PQV-130V

Description

Designed for production applications with simple ON/OFF operation.

Features

- Robust construction of one piece casting consisting of fixed jaw and vise bed
- Rigid casting of high tensile ductile iron FCD60JIS (Equal to GGG60) with 60kgs/mm² or 80,000 psi tensile strength
- Suitable for mass production runs on machine centre's, milling machines, drilling machines or special purpose machines
- Compact pneumatic mechanism design. No oil is required only a air supply
- Compact total length of vice with Max. clamping capacity
- Safety locking mechanism for unexpected termination of air supply. After pneumatic clamping. The work piece will be remain clamped firmly even without the air supply
- Easy and simple ON-OFF switch control for pneumatic operation
- Safety protection with Max. pneumatic clamping stroke is 4mm to prevent inserting operator's finger during clamping operation. (Stroke is 2mm best power capacity)
- Rapid ON-OFF only 1.5sec
- Free adjusting of Max. pneumatic clamping pressure from 0-1000kgf (4000) by air regulator, jaw opening 2mm is best clamping power capacity of workpiece
- Vise bed flame hardened to HRC45° to reduce up wear and maintain accuracy
- Down trust "semi-spherical segment" mechanism eliminates the jaw and work-piece lifting

Specifications

ORDER CODE	V341
MODEL	PQV-130V
D - Jaw Width (mm)	130
J - Jaw Opening (mm)	140
K - Jaw Height (mm)	55
Power (kgf)	0-1500
Air Pressure (kg/cm²)	1.5-7.0
Stroke (mm)	0-3
A (mm)	482
B (mm)	405
C (mm)	102
E (mm)	152
F (mm)	150
G (mm)	100
H (mm)	15
I (mm)	115
L (mm)	95
M (mm)	14
N (mm)	18
X (mm)	65
Y (mm)	100
Dimensions (L x W x H) (mm)	665 x 250 x 205
Nett Weight (kg)	38