

BUILDPRO TMQD625125

BuildPro™

2560 x 1250mm BuildPro Modular Welding Table - Nitrided Finish


Reversible Table Plates




BUILDPRO 2560 x 1250mm BuildPro Modular Welding Table - Nitrided Finish TMQD625125



Shown Welding with
Optional Accessories



Shown with Optional Accessories
Setting Up Go Cart Frame



Shown with Optional Accessories
Setting Up Sheetsteel



Shown with Optional
Accessories Setting Up Frame



Shown with Optional
Accessories Setting Up Frame 2




Shown with Optional
Accessories Setting Up Frame 3



Shown with Optional
Accessories Setting Up Frame 4



Shown with Optional
Accessories Setting Up Frame 5



Shown with Optional Accessories
and Joining Multiple Tables

Description

BuildPro® Models

NEW REVERSIBLE SELF-LOCATING TABLE PLATES!

The very practical, modular design of the BuildPro® Table makes it easy to set-up and tear down for job at hand, big or small. Save time and money by holding, positioning and locating quickly and easily with a wide variety of BuildPro® clamps and accessories.

In this economy, we know you need to be flexible and responsive to new business opportunities by reducing set-up time, improving consistency and work quality and remaining competitive in both pricing and delivery in a wide variety of jobs; short runs, volume production, prototypes, and multiple jobs in fabrication, repairs, and maintenance.

Accuracy:

Table flatness : 0.30mm / 914.4mm

Hole diameter : 16mm + 0.05mm

Hole spacing : 50mm ± 0.038mm

BUILDPRO 2560 x 1250mm BuildPro Modular Welding Table - Nitrided Finish TMQD625125

Plate thickness : 16mm $\pm$ 0.10mm

All BuildPro® Tables have 16mm thick steel plate with Ø16mm holes in a 50mm grid pattern. All tables, except BuildPro® MAX, have 40mm slots between plates.

Features

- The nitriding (heat-treating) process is a mechanical polish and post salt bath oxidative treatment. The benefits of this process included: Anti-Spatter, Corrosion Protection, and Resistance to wear, lubricity and fatigue strength
- Ø16mm holes
- 16mm thick plate
- 50 x 50mm grid pattern
- 900mm table height
- Includes legs

Specifications

ORDER CODE	W07721A
MODEL	TMQD625125
Table Top Finish (Type)	Nitrided Finish
Table Top Size (mm)	2560 x 1250
Table Height (mm)	900
Table Side Height (mm)	~
Top Plate Thickness (mm)	16
Grid Pattern (mm)	50 x 50
Table Hole Diameter (Ø)	16
Table Slots (mm)	40
Static Load Capacity (kg)	2500
Total W.L.L. (kg)	~
Number of Legs (No.)	~
Nett Weight (kg)	449