

## **HAFCO-WOODMASTER ST-254**



### **Table Saw**

**560 x 800mm Cast Iron Table**



## HAFCO-WOODMASTER Table Saw ST-254



Left View




Heavy Duty Rip Fence with Micro Adjustment



Rip fence Left View



Blade Guard with Dust Hose



Mitre Guide



Blade Angle Adjustment



Blade Adjustment Handles



Switch



Dust Chute



Shown with Table Support & Leg



Shown With Optional Sliding Table

### Description

The ST-254 Table Saw is a robust and smooth operating machine that is constructed largely from cast iron, the box section stand is made up of heavy gauge steel. Powered by a 2.2kW / 3hp - 240V 10-amp induction motor and Equipped with a 254mm blade a cutting depth of up to 75mm at 90° & 60mm at 45° can be achieved.

The cast iron table provides great strength and rigidity as well as a smooth user-friendly working surface. The micro adjustable rip fence is full length and cam locked solidly onto rails at the front and rear of the table and can be used on either side of the blade. The included mitre guide slides in T-slot grooves in the table which are also located on either side of the blade. Both the blade height and tilt controls have large handles that are conveniently located on front & side of the table saw.

The cast iron saw table also has solid cast iron extension tables on both left & right side of the table that measures an attractive 1170 x 800mm in total. Dust can be removed via a 100mm dust port outlet at rear of machine and the saw guard when connected to a suitable high-volume extraction system.

With the ability to accept an optional 1500mm sliding table set up (ST-254T) the ST-254 can be transformed into a handy little panel saw.

## HAFCO-WOODMASTER Table Saw ST-254

### Features

- Large 560 x 800mm cast iron table
- 1170 x 800mm with side extensions
- 254mm TCT saw blade
- 100mm dust collector port
- 75mm depth of cut at 90°
- 60mm depth of cut at 45°
- Dust proof magnetic switch
- Tilt arbor to 45°
- Powerful 2.2kW / 3hp, 240V induction motor
- Includes heavy duty rip fence with micro-adjustment, operated left or right of blade
- Dust extraction at the top of the blade as well as 100mm chute from the enclosed stand

### Includes

- Heavy duty rip fence
- Mitre guide
- Material push stick

### Specifications

|                                              |                    |
|----------------------------------------------|--------------------|
| <b>ORDER CODE</b>                            | W486               |
| <b>MODEL</b>                                 | ST-254             |
| <b>Blade Diameter (mm)</b>                   | Ø254               |
| <b>Table Size (W x H) (mm)</b>               | 560 x 800          |
| <b>Table Size With Extensions (mm)</b>       | 1170 x 800         |
| <b>Max. Depth Of Cut 90° &amp; 45° (mm)</b>  | 75 / 60            |
| <b>Scribe Blade Diameter (mm)</b>            | ~                  |
| <b>Tilt Arbor To 45°</b>                     | Yes                |
| <b>Sliding Table Stroke (mm)</b>             | ~                  |
| <b>Cross Cut with Flip Over Stop (mm)</b>    | ~                  |
| <b>Cross Cut with Extension Stop (mm)</b>    | ~                  |
| <b>Rip Capacity (mm)</b>                     | 950                |
| <b>Motor Power (kW / hp)</b>                 | 2.2 / 3            |
| <b>Voltage / Amperage (V / amp)</b>          | 240 / 10           |
| <b>Floor Space Required (W x D x H) (mm)</b> | 1350 x 1160 x 1100 |
| <b>Weight (nett) (kg)</b>                    | 190.5              |