

HAFCO GHD-38B



Industrial 4MT Geared Head Drilling Machine

Ø40mm Drilling Capacity




HAFCO Industrial 4MT Geared Head Drilling Machine GHD-38B

Image 2



Image 3




Image 4

Description

If you are looking for a little more of a series industrial drilling machine with a 4 morse taper spindle, then the GHD-38B geared head drilling machine is what you will need in your workshop to tackle all those medium to large drilling jobs.

With a great selection of 18 drilling speeds ranging from 50 – 1450rpm, and a generous drilling depth of 180mm, you will be able to accomplish many jobs that are required in any engineering & manufacturing production shops. Like all good drilling machines we offer in the market, this also has all the great necessity features required to make drilling holes as easy as possible. For e.g. thread tapping up to M24, powered auto feeds, coolant pump system, work light to shine directly onto your work and all the electrics are made to European standards for extra piece of mind.

Features

- Ideal for industrial workshop use
- Geared head drilling machine with 4 morse taper spindle
- Thread tapping with auto reverse
- Automatic feed range (0.1, 0.2mm/rev)
- 18 drilling speeds from 50-1450rpm
- Chuck guard with micro-switch
- Drill ejector incorporated in machine
- Coolant pump system with flexible hose
- Work light mounted in convenient location
- 40mm drill capacity with 180mm of Spindle travel
- Oil sight glass for geared head and feed gearbox
- Modern electrics to european CE standards
- Forward and reverse spindle switch with high and low speeds
- Emergency stop switch and overload protection
- Substantial heavy walled column ensuring greater rigidity
- Adjustable accurate depth setting with auto feed cut out for increased productivity
- Rack and pinion wind-up table
- T slotted work table and base

HAFCO Industrial 4MT Geared Head Drilling Machine GHD-38B

Includes

- 16mm drill chuck and arbor
- Coolant pump system
- Auto feed
- Tapping function
- Safety chuck guard
- Work light

Specifications

ORDER CODE	D1325
MODEL	GHD-38B
Drilling Capacity (mm)	Ø40
Thread Tapping Capacity (Metric)	M24
Spindle Taper (MT)	4
Spindle Travel (mm)	180
Throat Depth (mm)	350
Quill Diameter (mm)	75
Column Diameter (mm)	150
Spindle To Table (mm)	770
Spindle To Base (mm)	1320
Table (Type)	Square
Table Size (mm)	560 x 560
T-Slot Size (mm)	16
Automatic Quill Feed (mm/rev)	0.1, 0.2
Work Light (Includes)	Yes
Coolant System (Includes)	Yes
Spindle Speed Steps (No.)	18
Spindle Speed Range (rpm)	50 ~ 1450
Motor Power (kW / hp)	1.5 / 2
Voltage / Amperage (V / amp)	415
Full Height (mm)	2220
Nett Weight (kg)	615